

ADVERTISEMENT FOR BIDS

Notice is hereby given that sealed bids will be received by the City of Beverly, Burlington County, New Jersey, for the 2022 Road Program (the "Project") until **10:00 AM prevailing time on January 31, 2023**, at which time the bids will be opened and publicly read aloud in the office of the Municipal Clerk at 446 Broad Street, City of Beverly, New Jersey. Bids received after the designated time shall be deemed unresponsive and shall not be opened.

The Project generally includes roadway improvements on Laurel Street between Veteran's Drive and Warren Street in the City of Beverly, Burlington County, New Jersey complete in every detail as shown or specified, for the prices bid in the Proposal.

Drawings, specifications, and contract documents for the proposed Project, prepared by Environmental Resolutions, Inc., Consulting Engineers, have been filed in the Office of the City Engineer at 815 East Gate Drive – Suite 103, Mount Laurel, New Jersey 08054, and may be inspected by prospective bidders during normal business hours.

Bidders may obtain copies of the drawings, specifications and contract documents from the Office of the City Engineer upon payment of Fifty Dollars and Zero Cents (\$50.00). Checks should be made payable to Environmental Resolutions Inc. The payment for such documents is non-refundable. If the bidder requires the documents to be mailed to them, there is an additional Fifteen Dollars and Zero Cents (\$15.00) fee for postage.

Bids must be made on the standard Bid form contained within the drawings, specifications, and contract documents, in the manner designated therein and required by the specifications. Further, bids must be enclosed in a sealed envelope bearing the name and address of the bidder and the Project title on the outside, and addressed to: Beverly City Administrator, Frank Costello Municipal Building, 446 Broad Street, City of Beverly, New Jersey 08010.

Each bid must be accompanied by (i) all documents listed on the Bid Document Submission Checklist, as applicable, and (ii) a bid guarantee in an amount not less than Ten Percent (10%) of the total bid price as established in the Bid, not to exceed Twenty Thousand Dollars and Zero Cents (\$20,000.00). The bid guarantee must be in the form of a bid bond, certified check, or cashier's check, must be drawn to the order of the City of Beverly and must be delivered simultaneous with the sealed bid.

Bidders are required to comply with the requirements of N.J.S.A. 10:5-31 et seq., N.J.A.C.17:27, and all other applicable laws referenced within the drawings, specifications and contract documents.

This project is being partially funded by an NJDOT grant.

The City of Beverly reserves the right to (i) reject all bids pursuant to N.J.S.A. 40A:11-13.2 and (ii) to waive minor informalities and/or non-material exceptions in any bid should it be in the interest of the City of Beverly to do so. Further, the City of Beverly shall reject any bid that contains material nonconformities or conditions or which is materially nonresponsive. In the event the City of Beverly does not reject all bids as permitted under N.J.S.A. 40A:11-13.2, in accordance with N.J.S.A. 40A:11-4, and other applicable laws, the Project will be awarded to the lowest responsible bidder.

By order of the Council of the City of Beverly of Beverly, Burlington County, New Jersey.

Project Quantities as of December 20, 2022

Item	Description	Quantity	
Base Bid – Veterans Street to Sta. 17+00			
1.	Excavate Roadway	1050	SY
2.	Remove Concrete	760	SY
3.	Remove Concrete Curb	800	LF
4.	Remove Asphalt	15	SY
5.	Remove Manhole	2	UN
6.	Remove Sign and Post	2	UN
7.	Remove Tree, 12” Diameter or Greater (If & Where Directed)	-	UN
8.	I-8 Soil Aggregate (If & Where Directed)	240	CY
9.	Milling, 0”-4” Thick	1100	SY
10.	HMA Surface Course, 9.5M64, 1.5” Thick	100	TON
11.	HMA Base Course, 19M64, 1.5” Thick	170	TON
12.	Install Concrete Swale, 8” Thick	3	SY
13.	Remove and Replace Concrete Apron, 6” Thick	30	SY
14.	Install Concrete Apron, 6” Thick	14	SY
15.	Install Concrete Sidewalk, 4” Thick	65	SY
16.	Remove and Replace Concrete Sidewalk, 4” Thick	30	SY
17.	Construct Concrete Curb	230	LF
18.	Reconstruct Inlet, Type ‘B’	-	UN
19.	Construct Inlet, Type ‘B’	1	UN
20.	Construct Inlet, Type ‘Double B’	1	UN
21.	Construct Doghouse Inlet, Type ‘B’	1	UN
22.	Convert Inlet, Type ‘B’ to Inlet, Type ‘E’	1	UN
23.	Construct Inlet, Type ‘A’	1	UN
24.	Construct Inlet, Type ‘D’	2	UN
25.	Remove 18” RCP & Construct 18” PCPP	210	LF
26.	Remove 18” RCP & Construct Dual 15” PVC	220	LF
27.	Construct 12” DIP	30	LF
28.	Construct Storm Manhole, 0’-6’ Deep	2	UN
29.	Install Crosswalk	2	UN
30.	Curb Painting	-	LF
31.	Detectable Warning Surface	40	SF
32.	ADA Ramp Sidewalk, 6” Thick	16	SY
33.	Topsoil & Seed, 4” Thick	1700	SY
34.	Subbase DGA, 6” Thick (If & Where Directed)	10	SY
35.	Asphalt Price Adjustment	\$100.00	DOL
36.	Fuel Price Adjustment	\$100.00	DOL
Alternate #1 – Sta. 17+00 to Sta. 18+16			
2A.	Remove Concrete	47	SY
5A.	Remove Manhole	1	UN
9A.	Milling, 0”-4” Thick	432	SY
10A.	HMA Surface Course, 9.5M64, 1.5” Thick	45	TON
11A.	HMA Base Course, 19M64, 1.5” Thick	74	TON
16A.	Remove and Replace Concrete Sidewalk, 4” Thick	40	SY
17A.	Construct Concrete Curb	99.5	LF

24A. Construct Inlet, Type 'D'	2	UN
25A. Remove 18" RCP & Construct 18" PCPP	108	LF
27A. Construct 12" DIP	30	LF
28A. Construct Storm Manhole, 0'-6' Deep	1	UN
29A. Install Crosswalk	4	UN
30A. Curb Painting	20	LF
31A. Detectable Warning Surface	64	SF
32A. ADA Ramp Sidewalk, 6" Thick	40	SY
34A. Subbase DGA, 6" Thick (If & Where Directed)	10	TON

Alternate #2 – Sta. 18+16 to Sta. 22+00

2B. Remove Concrete	250	SY
4B. Remove Asphalt	10	SY
5B. Remove Manhole	2	UN
7B. Remove Tree, 12" Diameter or Greater (If & Where Directed)	1	UN
9B. Milling, 0"-4" Thick	1350	SY
10B. HMA Surface Course, 9.5M64, 1.5" Thick	130	TON
11B. HMA Base Course, 19M64, 1.5" Thick	210	TON
13B. Remove and Replace Concrete Apron, 6" Thick	60	SY
15B. Install Concrete Sidewalk, 4" Thick	10	SY
16B. Remove and Replace Concrete Sidewalk, 4" Thick	55	SY
17B. Construct Concrete Curb	410	LF
24B. Construct Inlet, Type 'D'	2	UN
25B. Remove 18" RCP & Construct 18" PCPP	260	LF
27B. Construct 12" DIP	30	LF
28B. Construct Storm Manhole, 0'-6' Deep	1	UN
29B. Install Crosswalk	4	UN
31B. Detectable Warning Surface	64	SF
32B. ADA Ramp Sidewalk, 6" Thick	40	SY
33B. Topsoil & Seed, 4" Thick	35	SY
34B. Subbase DGA, 6" Thick (If & Where Directed)	10	TON

Alternate #3 – Sta. 22+00 to Warren Street

2C. Remove Concrete	100	SY
7C. Remove Tree, 12" Diameter or Greater (If & Where Directed)	1	UN
9C. Milling, 0"-4" Thick	550	SY
10C. HMA Surface Course, 9.5M64, 1.5" Thick	55	TON
11C. HMA Base Course, 19M64, 1.5" Thick	90	TON
13C. Remove and Replace Concrete Apron, 6" Thick	25	SY
16C. Remove and Replace Concrete Sidewalk, 4" Thick	20	SY
17C. Construct Concrete Curb	110	LF
18C. Reconstruct Inlet, Type 'B'	2	UN
25C. Remove 18" RCP & Construct 18" PCPP	200	LF
30C. Curb Painting	60	LF
34C. Subbase DGA, 6" Thick (If & Where Directed)	10	TON